



Non-Ferrous Cutting Saws

A specially formulated carbide makes cutting all kinds of non-ferrous metal simple and easy. Cut sheets, extrusions, or light solids of aluminum, copper, and brass. Clamp material firmly and lubricate blade with cutting fluid. Do not use on steel or other ferrous metals.

DIAMETER	TEETH	DESIGN	KERF	PLATE	BORE & PINS	HOOK	ORDER ID	LIST PRICE
4"	20T	TCG	.095"	.062"	3/4"	0	NF4200	64.80
7 1/4"	40T	TCG	.118"	.087"	5/8"	-5	NF72540	81.00
7 1/4"	60T	TCG	.087"	.058"	5/8"	0	NF760	81.00
8"	48T	TCG	.126"	.094"	5/8"	-5	NF848	103.95
8"	60T	TCG	.126"	.094"	5/8"	-5	NF860	118.80
8"	80T	TCG	.130"	.083"	5/8"	5	NF880	137.70
9"	60T	TCG	.134"	.102"	5/8"	-5	NF960	140.40
10"	60T	TCG	.134"	.102"	5/8"	-5	NF1060	135.00
10"	60T	TCG	.118"	.087"	5/8"	-5	NF1060EX	108.00
10"	80T	TCG	.134"	.110"	5/8"	-5	NF1080	167.40
10"	80T	TCG	.118"	.087"	5/8"	-5	NF1080EX	124.20
10"	100T	TCG	.134"	.110"	5/8"	-5	NF1010	183.60
10"	100T	TCG	.118"	.094"	5/8"	-5	NF1010118	156.60
10"	120T	FTG	.087"	.055"	5/8"	10	NF1012	189.00
300mm	90T	TCG	3.2mm	2.4mm	32mm	-5	NF30090	186.30
300mm	100T	TCG	3.2mm	2.6mm	30mm	-5	NF3003010	194.40
12"	80T	TCG	.142"	.118"	1"	-5	NF1280	199.80
12"	80T	TCG	.126"	.110"	5/8"	-5	NF1280P	199.80
12"	100T	TCG	.142"	.118"	1"	-5	NF1210	210.60
12"	100T	TCG	.126"	.110"	5/8"	-5	NF1210P	210.60
12"	120T	TCG	.126"	.110"	1"	-5	NF1212	237.60
330mm	90T	TCG	3.4mm	2.8mm	32mm	-5	NF3303290	237.60
14"	80T	TCG	.150"	.126"	1"	-5	NF1480	243.00
14"	100T	TCG	.157"	.130"	1"	-5	NF1410	251.10
14"	120T	TCG	.157"	.130"	1"	-5	NF1412	297.00
14"	120T	TCG	.146"	.118"	5/8"	-5	NF1412P	297.00
350mm	84T	TCG	3.2mm	2.2mm	32mm, 4/12/64	-5	NF3503284	221.40
350mm	84T	TCG	3.6mm	3.0mm	40mm	-5	NF3504084	229.50
350mm	108T	TCG	3.2mm	2.2mm	32mm, 4/12/64	-5	NF35032108	243.00
350mm	100T	TCG	3.8mm	3.2mm	32mm	0	NF38032100	232.20
15"	100T	TCG	.126"	.102"	1"	-5	NF1510	229.50
16"	60T	TCG	.165"	.134"	1"	-5	NF1660	259.20
16"	100T	TCG	.165"	.134"	1"	-5	NF1610	302.40
16"	120T	CTC	.157"	.130"	1"	-5	NF1612	367.20
420mm	96T	TCG	4.2mm	3.4mm	30mm	-5	NF4203096	332.10
425mm	72T	TCG	4.5mm	4.0mm	50mm	10	NF4255072	405.00
18"	60T	TCG	.230"	.150"	1"	-5	NF1860	340.20
18"	72T	TCG	.176"	.142"	1 1/2"	0	NF1872MS*	353.70
18"	100T	TCG	.176"	.138"	1"	-5	NF1810	375.30
18"	120T	CTC	.180"	.150"	1"	-5	NF1812	434.70
500mm	100T	TCG	.180"	.150"	30mm	0	NF5003010	405.00
500mm	120T	TCG	4.6mm	3.8mm	30mm, 4/12/64	-5	NF5003012	461.70
500mm	120T	TCG	4.6mm	3.8mm	32mm	-5	NF5003212	461.70

continued on the next page



Non-Ferrous Cutting Saws (cont.)

A specially formulated carbide makes cutting all kinds of non-ferrous metal simple and easy. Cut sheets, extrusions, or light solids of aluminum, copper, and brass. Clamp material firmly and lubricate blade with cutting fluid. Do not use on steel or other ferrous metals. Order ID only shows 1" arbor size.

DIAMETER	TEETH	DESIGN	KERF	PLATE	BORE & PINS	HOOK	ORDER ID	LIST PRICE
20"	60T	TCG	.180"	.150"	1"	0	NF2060	351.00
20"	60T	TCG	.180"	.150"	1 1/2"	0	NF2060MS*	356.40
20"	72T	TCG	.180"	.150"	1 1/2"	0	NF2072MS*	359.10
20"	80T	TCG	.180"	.150"	1"	-5	NF2080	361.80
20"	100T	TCG	.180"	.150"	1"	-5	NF2010	399.60
20"	120T	TCG	.180"	.150"	1"	-5	NF2012	453.60
20"	160T	TCG	.180"	.150"	1"	-5	NF2016	523.80
550mm	100T	TCG	4.6mm	3.8mm	30mm	-5	NF5503010	693.90
22"	60T	TCG	.180"	.150"	1 1/2"	5	NF2260MS*	585.90
22"	96T	TCG	.190"	.155"	40mm, 4/12/64	-5	NF2296ES	685.80
22"	100T	TCG	.180"	.150"	1"	-5	NF2210	653.40
22"	120T	TCG	.180"	.150"	1"	-5	NF2212	707.40
24"	60T	TCG	.205"	.165"	1 1/2"	5	NF2460MS*	623.70
24"	72T	TCG	.205"	.165"	1"	5	NF2472	634.50
24"	72T	TCG	.205"	.165"	1 1/2"	5	NF2472MS*	639.90
24"	80T	TCG	.205"	.165"	1"	-5	NF2480	650.70
24"	100T	TCG	.205"	.165"	1"	-5	NF2410	680.40
24"	120T	TCG	.205"	.165"	1"	-5	NF2412	712.80
24"	160T	TCG	.205"	.165"	1"	-5	NF2416	788.40
24"	160T	TCG	.205"	.165"	30mm	-5	NF243016	796.50

*For Metlsaw plate saws. ** We sell wax sticks to lubricate non-ferrous blades, which improves cutting efficiency



Melamine Saws

A higher angle on the top bevel (+30°) gives this saw an extra sharp shearing action to slice through single or double sided laminates without chipping. These blades are good for laminates, melamine, coreboard and other composite materials. Made with Micro-Sheen C-4 sub-micron carbide for an extended life.

DIAMETER	TEETH	DESIGN	KERF	PLATE	BORE	HOOK	ORDER ID	LIST PRICE
8"	64T	HATB	.118"	.079"	5/8"	-5	LM864	110.70
180mm	36T	**HFV	2.9mm	2.0mm	30mm	-5	LM18036HF	132.50
220mm	64T	HATB	3.0mm	2.2mm	30mm/2 PH	-5	LM22064*	124.20
220mm	42T	**HF	3.2mm	2.2mm	30mm/2 PH	10	LMH22042	148.50
250mm	80T	HATB	3.2mm	2.2mm	30mm/2 PH	-5	LM2503080	113.40
10"	48T	**HFV	.126"	.087"	5/8"	10	LM1048HF	113.40
10"	80T	HATB	.126"	.087"	5/8"	-5	LM1080	113.40
10"	80T	TCG	.126"	.087"	5/8"	-5	LM1080TCG	126.90
10"	80T	HATB	.102" max. cut 1"	.071"	5/8"	0	LM1080X	126.90
300mm	60T	**HF	3.2mm	2.2mm	30mm/2 PH	10	LMH30060	180.90
300mm	80T	HATB	3.2mm	2.2mm	30mm/2 PH	-5	LM30080*	175.50
300mm	100T	HATB	3.2mm	2.2mm	30mm/2 PH	-5	LM30010*	191.70
12"	80T	HATB	.134"	.094"	1"	-5	LM1280	172.80
12"	100T	HATB	.134"	.094"	1"	-5	LM1210	194.40
14"	100T	HATB	.142"	.110"	1"	-5	LM1410	226.80
16"	100T	HATB	.158"	.118"	1"	-5	LM1610	234.90

* For use on Holz-Her or Striebig vertical panel saw. ** Hollow Face Pinholes on 220mm are 2/7/42mm & on 300mm are 2/7/42 + 2/10/60mm